



/

personnel. Failure to do so may lead to serious risks to personnel safety and potential loss of property.

M

Please refer to the M series hardware manual for more detailed information.

Hechuan Technology)		2AD+1DA (Analog 2AD+1DA)		BD BD Optional BD card)	
MXB	M M-Series optional expansion	MA03			
		200	M200 M200 series optional card	XXXX	0-9/A-Z/ (N/A)

expansion card	HCMXB-MA03-200-BD	HCM211-20MR-A HCM211-20MT4-A HCM211-32MR-A HCM211-32MT6-A HCM211-42MR-A HCM211-42MT8-A HCM211-60MR-A HCM211-60MT10-A HCM212-32MT4-A HCM212-60MT8-A	2	1	
----------------	-------------------	---	---	---	--

Operating environment		≤ 2000m	
Operating temperature	0~55	Operating temperature	0~55
Storage temperature	-25~70	Storage temperature	-25~70
	10~95%RH		10~95%RH (non-condensing)
Vibration resistance	5~150Hz X/Y/Z 2	1g/3.5mm	5~150Hz (X/Y/Z direction, 1g /3.5mm displacement)
			Level 2
			Natural air cooling
Enclosure material	IP20		IP20
			Self-extinguishable

*Note: If the equipment is used in a manner not specified by the manufacturer, the protection provided by the equipment may be impaired.



CN



1+	IN	V11+			
channel 1+)					